


Artikelnummer/Itemnumber: 478B

Absperr-Stilpfosten Serie 478B Ø 76 mm, ortsfest, zum Einbetonieren mit Erdanker, Gesamtlänge ca. 1300 mm, ohne Verschluss, ohne Öse



Ornamental bollard Series 478B Ø 76 mm, stationary, for casting in concrete with ground anchor, total length approx. 1300 mm, without lock, without eyelet



Artikelbeschreibung:

Absperr-Stilpfosten aus Stahlrundrohr Ø 76 mm ca. 950 mm Überflur, feuerverzinkt und anthrazitgrau (RAL 7016) beschichtet, ortsfest, zum Einbetonieren mit Erdanker, Gesamtlänge ca. 1300 mm, ohne Verschluss, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 7,50 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Ornamental bollard of steel tube Ø 76 mm approx. 950 mm above ground, hot-dip galvanized and coated anthracite-grey (RAL 7016), stationary, for casting in concrete with ground anchor, total length approx. 1300 mm, without lock, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 7,50 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated